

# DATASHEET

## AU-FTU

Article number: 29100



### Product description

The Attema Universal FTU (AU-FTU) is a compact fiber termination unit. It can be applied as a final fiber termination point at residential or business fiber installations. The AU-FTU is the connection between the fiber network and the Network Termination Unit (NTU). The NTU can be connected with the AU-FTU by using a single mode simplex SC patchcord. The AU-FTU is suitable for fiber optic cables with max. 2 fibers. It provides mechanical protection and fiber management and easy to install. There is also a possibility to seal off the connections in order to prevent unauthorized opening.

### Features and Benefits

- Easy to install
- Orderly assembly sequence
- Universal applicable (for indoor use)
- Multiple sealable (lid and 2 connector-holders)
- Suitable for most connectors SC / APC
- Suitable for splice protectors ANT, mini heatshrink and heatshrink Ø2,4x45mm
- Integrated cable retention
- Installation manual available at [www.attema.com](http://www.attema.com)

### Technical characteristics

Material:	Molded Plastic, halogen-free
Dimensions :	H=150mm W=80mm D=38mm
Weight:	0,2 kg
Colour:	White
FTU:	White
Connector-holders:	Grey
Dropcable diameters:	max. Ø 8 mm
Number of cable ports in:	1
Number of adapters SC / APC:	2
Splice tray capacity:	2 splice protectors ANT/mini heatshrink or heatshrink Ø2,4x45mm
Fiber bending radius:	R = 23mm
Looping length of fibers:	25 cm

Package consists of recyclable materials and is clearly labelled with Attema article number 29100 and the description 8 pcs / carton.

END OF DATASHEET

[www.attema.com](http://www.attema.com)